





孔位	A	B	C	D
2	1.00	3.10	6.85	8.15
3	2.00	4.10	7.85	9.15
4	3.00	5.10	8.85	10.15
5	4.00	6.10	9.85	11.15
6	5.00	7.10	10.85	12.15
7	6.00	8.10	11.85	13.15
8	7.00	9.10	12.85	14.15
9	8.00	10.10	13.85	15.15
10	9.00	11.10	14.85	16.15
11	10.00	12.10	15.85	17.15
12	11.00	13.10	16.85	18.15
13	12.00	14.10	17.85	19.15
14	13.00	15.10	18.85	20.15
15	14.00	16.10	19.85	21.15
16	15.00	17.10	20.85	22.15
17	16.00	18.10	21.85	23.15
18	17.00	19.10	22.85	24.15
19	18.00	20.10	23.85	25.15
20	19.00	21.10	24.85	26.15
21	20.00	22.10	25.85	27.15
22	21.00	23.10	26.85	28.15
23	22.00	24.10	27.85	29.15
24	23.00	25.10	28.85	30.15
25	24.00	26.10	29.85	31.15
26	25.00	27.10	30.85	32.15
27	26.00	28.10	31.85	33.15
28	27.00	29.10	32.85	34.15
29	28.00	30.10	33.85	35.15
30	29.00	31.10	34.85	36.15

性能:		修订		修改摘要		签名		日期	
REV	MARK	REV	MARK	REVISION	DESCRIPTION	SIGNATURE		DATE	
AO				NEW	DRG	WANG		2016-03-12	

性能:  
额定电流: 0.4A  
额定电压: 50V  
耐压: 200V  
接触电阻: ≤20mΩ  
绝缘电阻: 500MΩ  
工作温度: -20℃~+85℃

塑件(材质): LCP, UL94V-0  
锁扣(材质): LCP, UL94V-0  
插簧(材质): 磷青铜, 镀锡/镀金  
焊片(材质): 磷青铜, 镀锡/镀金



		深圳市华德共创科技有限公司 Shenzhen Huade co-create Technology Co.,LTD 电话: 0755-27129737      传真: 0755-29940187					
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				 		TITLE: 产品名称: 1.0mm FPC (A型)下接(H=2.0)	
X.X    ±0.30	X.X*    ±3°	APPD: 核准: XIE		PART NO: 产品编号: 1.0K-MX-nPWB			
X.XX   ±0.20	X.XX*   ±2°	CHECK: 校对: WANG	DATE	SCALE	UNIT	CODE NUMBER	
X.XXX   ±0.10	X.XXX*   ±1°	DRAW: 绘图: WANG	2016-03-12	1:1	mm	A001	